ON-CAMERA LIGHT

ULA-1

Water resistant IP55 on-camera light Akurat ULA-1 with movable LED matrix, emitting light with a very high color rendering index CRI.

Placing the LED matrix on the hinge with adjustable frictional force, makes possible to tilt the lamp, but also to fold the matrix to a horizontal position to facilitate movement operator with the camera with the light and prevent mechanical damage of the fixture and the camera.
The lamp is made in IP55 ingress protection class, which means the total resistance to rain and dust.
The mounting adapter of the ULA-1 is compatible with the Akurat 10mm® fastening system. You can configure the light to be attached to the camera or to other accessories, selecting the appropriate elements from the wide list of the fixing accessories of this system. It is possible to configure the mount to the photo-shoe socket or to the 1/4 inch threaded connections, with the option of quick mounting and disassembly of accessories.
The light is equipped with a power switch and brightness and color temperature controllers. Sealed movable controls and power connection are high-quality industrial components for durability and high reliability.
Aluminum alloy and carbon composite were used for the construction of the ULA-1 , thanks to which the weight of the fixture is up to 200g.
Many accessories like cables and magnetic barndoors with diffuser are available as an option.
Made in EU (Poland)

Technical Specification

Photometric Parameters		
max illuminance at distance:		
0,6m	1030 lx	
1.0m	360 lx	
1,2m	242 lx	
1,8m	110 lx	
2,4m	63 lx	
angle of flux (50% max illuminance)	120°	
CCT range	3200-5600 K	tungsten (+0K, -250K) /daylight (+0K -300K)
color rendering index CRI	Ra >95	Ra>98 in V-White® version
Electrical Parameters		
type of power connection	M8 4 pin	D-Tap, 5.5/2.1 or other cables available
nominal power voltage	6-16 V	DC
max power consumption	11 W	
max power voltage	18 V	absolute maximum
min power voltage	5,8 V	
Mechanical Parameters		
amount of sources of light (LEDs)	77	
dimensions:		
width	105 mm	
height	130 mm	
height with matrix folded	58 mm	
type of mounting adapter	Akurat 10mm®	
basic materials	aluminum/carbon composit	
weight	200 g	
Environmental parameters		
operating temperature	-20+40°C	
storage temperature	-40+80°C	
IP class	IP55	

AKURAT LIGHTING

BBP Light bv
Abberdaan 194 - 196 1046 AB Amsterdam
+31 (0) 20 - 690 98 98 info@bbplight.com www.bbplight.com

ON-CAMERA LIGHT

LiLA-1

BBP Light bv
Abberdaan 194 - 196 1046 AB Amsterdam
+31 (0) 20 - 690 98 98 info@bbplight.com www.bbplight.com

AKURAT LIGHTING