



TITAN POWER BOX

FP1-PWB

Power Supply to charge up to 10 tubes that offers optional wired data transfer option for DMX, Artnet and sACN.
(Not suitable for Hyperion Tube)



Electrical

Input Voltage:
90~250 VAC

Current:
4.4A@115VAC, 3A@230VAC

Output Voltage:
10 x 24VDC

Output Current:
10 x 2A

Power in
Via Powercon True1

Power out
Via Powercon True1

Data

Data Input by:

- XLR-DMX
- Art-Net (1 Universe)
- sACN (1 Universe)

IP Address can be selected between 2.x, 10.x and DHCP.

Universe ID can be set by web-interface or pushbutton (by button only 1-16).

Output Data

DMX via DC sockets

Wireless Data

n/a

Data Sockets

5-pin XLR in+out, RJ45 input

Construction

Housing

Aluminium

IP Rating

IP20

Operating Temperature

0-40 °C | 32-104 °F

Weight

3.8kg | 8.37lbs

Dimensions

321 x 125 x 90.7mm

12.63 x 4.92 x 3.57 inches

Environment

Indoor

Accessories

1 x Powercon True1 AC cable
(Included)

8 x short DC cables
(Included)

5m/10m/15m Power Data Combination
cables

Item code: FP1-PWB-CAB-5/10/15

Drawings

